



Material Safety Data Sheet

Product Name **Asset Protector Spray**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name **Asset Protector**
Address Newhaven Enterprise Centre, Denton Island, Newhaven, East Sussex, BN9 9BA, UK
Telephone 0845 1800 111
Fax 0845 1800 552
Emergency 0845 1800 111
Web Site www.assetprotector.co.uk
Synonym(s) Asset Protector Spray • LS - MANUFACTURER'S PRODUCT CODE
Use(s) CORROSION PREVENTION • LEATHER CONDITIONER • LUBRICANT • WATER PROOFING
SDS Date 09 Aug 2010

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN No. None Allocated **DG Class** None Allocated **Subsidiary Risk(s)** None Allocated
Packing Group None Allocated **Hazchem Code** None Allocated

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	Not Available	64742-48-9	40-60%
LANOLIN	Not Available	8006-54-0	10-60%

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

Advice to Doctor Contact Poisons Information Centre (13 11 26).

Product Name **Asset Protector Spray**

5. FIRE FIGHTING MEASURES

Flammability	Combustible. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.
Fire and Explosion	Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
Extinguishing	Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.
Hazchem Code	None Allocated

6. ACCIDENTAL RELEASE MEASURES

Spillage	Contact emergency services where appropriate. Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbant material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all ignition sources.
-----------------	--

7. STORAGE AND HANDLING

Storage	Store in a cool, dry, well ventilated area, removed from oxidising agents, acids, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should have appropriate ventilation systems. Store as a Class C1 Combustible Liquid (AS1940). Also store removed from moisture.
Handling	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Stdts	No exposure standard(s) allocated.
Biological Limits	No biological limit allocated.
Engineering Controls	Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Maintain vapour levels below the recommended exposure standard.
PPE	Wear splash-proof goggles and rubber or PVC gloves. When using large quantities or where heavy contamination is likely, wear: coveralls. Where an inhalation risk exists, wear: a Type A (Organic vapour) respirator. With prolonged use, wear: viton (R) gloves.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	LIGHT BROWN LIQUID	Solubility (water)	INSOLUBLE
Odour	SLIGHT ODOUR	Specific Gravity	0.94
pH	NOT AVAILABLE	% Volatiles	NOT AVAILABLE
Vapour Pressure	NOT AVAILABLE	Flammability	CLASS C1 COMBUSTIBLE
Vapour Density	5 (Air = 1)	Flash Point	63°C (cc)
Boiling Point	110°C to 140°C	Upper Explosion Limit	60%
Melting Point	NOT AVAILABLE	Lower Explosion Limit	0.8 %
Evaporation Rate	NOT AVAILABLE		
Autoignition Temperature	> 200°C		

Product Name **Asset Protector Spray**

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to Avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to Avoid	Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), heat and ignition sources.
Hazardous Decomposition Products	May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.
Hazardous Reactions	Polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	Low toxicity. This product has the potential to cause adverse health effects with direct eye contact, prolonged skin contact or vapour inhalation in poorly ventilated areas. Use safe work practices to avoid eye or skin contact and vapour generation - inhalation.
Eye	Low to moderate irritant. Contact may result in irritation, lacrimation, pain and redness.
Inhalation	Irritant. Over exposure may result in irritation of the nose and throat, coughing and headache. High level exposure may result in nausea, dizziness and drowsiness.
Skin	Low irritant. Prolonged or repeated contact may result in mild irritation, rash and dermatitis.
Ingestion	Low toxicity. Ingestion of large quantities may result in nausea, vomiting, abdominal pain, diarrhoea, and drowsiness. Aspiration may result in chemical pneumonitis and pulmonary oedema.
Toxicity Data	No LD50 data available for this product.

12. ECOLOGICAL INFORMATION

Environment	Aliphatic hydrocarbons behave differently in the environment depending on their size. WATER: Light aliphatics volatilise rapidly from water (half life - few hours). Bioconcentration should not be significant. SOIL: Light aliphatics biodegrade quickly in soil and water, heavy aliphatics biodegrade very slowly. ATMOSPHERE: Vapour-phase aliphatics will degrade by reaction with hydroxyl radicals.
--------------------	---

13. DISPOSAL CONSIDERATIONS

Waste Disposal	For small amounts absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer for additional information if larger amounts are involved. Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Shipping Name	None Allocated			
UN No.	None Allocated	DG Class	None Allocated	Subsidiary Risk(s) None Allocated
Packing Group	None Allocated	Hazchem Code	None Allocated	

15. REGULATORY INFORMATION

Poison Schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).
AICS	All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Additional Information	WORK PRACTICES - SOLVENTS: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.
-------------------------------	---

Product Name Asset Protector Spray

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

EXPOSURE STANDARDS - TIME WEIGHTED AVERAGE (TWA) or WES (WORKPLACE EXPOSURE STANDARD) (NZ): Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m³ - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

COLOUR RATING SYSTEM: RMT has assigned all Chem Alert reports a colour rating of Green, Amber or Red for the sole purpose of providing users with a quick and easy means of determining the hazardous nature of a product. Safe handling recommendations are provided in all Chem Alert reports so as to clearly identify how users can control the hazards and thereby reduce the risk (or likelihood) of adverse effects. As a general guideline, a Green colour rating indicates a low hazard, an Amber colour rating indicates a moderate hazard and a Red colour rating indicates a high hazard.

While all due care has been taken by RMT in the preparation of the Colour Rating System, it is intended as a guide only and RMT does not provide any warranty in relation to the accuracy of the Colour Rating System. As far as is lawfully possible, RMT accepts no liability or responsibility whatsoever for the actions or omissions of any person in reliance on the Colour Rating System.

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss,

GREEN

Product Name **Asset Protector Spray**

injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

SDS Date 09 Aug 2010

End of Report